



Eaton Analytical

750 Royal Oaks Drive, Suite 100
Monrovia, California 91016-3629
Tel: (626) 386-1100
Fax: (626) 386-1101
1 800 566 LABS (1 800 566 5227)



Laboratory Report

for

Horsham Water & Sewer Authority
617 Horsham Road
Horsham, PA 19044
Attention: Tina M. O'Rourke
Fax: (215) 672-8065

Date of Issue
07/10/2014


EUROFINS EATON
ANALYTICAL

TDF: Thomas.D.French
Project Manager

Report: 487436
Project: UCMR3
Group: PA1460033/Horsham
W&SA GW

- * Accredited in accordance with TNI 2009 and ISO/IEC 17025:2005.
- * Laboratory certifies that the test results meet all **TNI 2009 and ISO/IEC 17025:2005** requirements unless noted under the individual analysis.
- * Following the cover page are State Certification List, ISO 17025 Accredited Method List, Acknowledgement of Samples Received, Comments, Hits Report, Data Report, QC Summary, QC Report and Regulatory Forms, as applicable.
- * Test results relate only to the sample(s) tested.

STATE CERTIFICATION LIST

State	Certification Number	State	Certification Number
Alabama	41060	Mississippi	Certified
Alaska	CA00006	Montana	Cert 0035
Arizona	AZ0778	Nebraska	Certified
Arkansas	Certified	Nevada	CA00006-2014-1
California-Monrovia-ELAP	2813	New Hampshire *	2959
California-Colton- ELAP	2812	New Jersey *	CA 008
California-Folsom- ELAP	2820	New Mexico	Certified
Colorado	Certified	New York *	11320
Connecticut	PH-0107	North Carolina	06701
Delaware	CA 006	North Dakota	R-009
Florida *	E871024	Oregon (Primary AB) *	ORELAP 4034
Georgia	947	Pennsylvania *	68-565
Guam	14-003r	Rhode Island	LAO00326
Hawaii	Certified	South Carolina	87016
Idaho	Certified	South Dakota	Certified
Illinois *	200033	Tennessee	TN02839
Indiana	C-CA-01	Texas *	T104704230-14-6
Kansas *	E-10268	Utah *	CA000062014-7
Kentucky	90107	Vermont	VT0114
Louisiana *	LA140009	Virginia *	460260
Maine	CA0006	Washington	C838
Maryland	224	West Virginia	9943 C
Commonwealth of Northern Marianas Is.	MP0004	Wisconsin	998316660
Massachusetts	M-CA006	Wyoming	8TMS-L
Michigan	9906	EPA Region 5	Certified
Los Angeles County Sanitation Districts	10264		

* NELAP/TNI Recognized Accreditation Bodies

ISO 17025 Accredited Method List

The tests listed below are accredited and meet the requirements of ISO 17025 as verified by the ANSI-ASQ National Accreditation Board/ACLASS.
Refer to Certificate and scope of accreditation (AT 1807) found at: <http://www.eatonanalytical.com>

SPECIFIC TESTS	METHOD OR TECHNIQUE USED	Drinking Water	Food & Beverage	Waste Water
1,4-Dioxane	EPA 522	x	x	
2,3,7,8-TCDD	Modified EPA 1613B	x	x	
Acrylamide	In House Method	x	x	
Alkalinity	SM 2320B	x	x	x
Ammonia	EPA 350.1		x	x
Ammonia	SM 4500-NH3 H (18th)		x	x
Anions and DBPs by IC	EPA 300.0	x	x	x
Anions and DBPs by IC	EPA 300.1	x	x	
Asbestos	EPA 100.2	x		
Bicarbonate Alkalinity as HCO ₃	SM 2330B	x	x	x
BOD / CBOD	SM 5210B		x	x
Bromate	In House Method	x	x	
Carbamates	EPA 531.2	x	x	
Carbonate as CO ₃	SM 2330B	x	x	x
Carbonyls	EPA 556	x	x	
COD	EPA 410.4 / SM 5220D			x
Chloramines	SM 4500-CL G	x	x	x
Chlorinated Acids	EPA 515.4	x	x	
Chlorinated Acids	EPA 555	x	x	
Chlorine Dioxide	SM 4500-CLO ₂ D	x	x	
Chlorine - Total/Free/ Combined Residual	SM 4500-Cl G	x	x	x
Conductivity	EPA 120.1			x
Conductivity	SM 2510B	x	x	x
Corrosivity (Langelier Index)	SM 2330B	x	x	
Cyanide, Amenable	SM 4500-CN G	x		x
Cyanide, Free	SM 4500CN F	x	x	x
Cyanide, Total	EPA 335.4	x	x	x
Cyanogen Chloride (screen)	In House Method	x	x	
Diquat and Paraquat	EPA 549.2	x	x	
DBP/HAA	SM 6251B	x	x	
Dissolved Oxygen	SM 4500-O G		x	x
E. Coli (MTF/EC+MUG)		x		
E. Coli (CFR 141.21(f)(6)(i))			x	x
E. Coli (SM 9223)				x
E. Coli (Enumeration) (SM 9221 B.1/ SM 9221F)		x	x	
E. Coli (Enumeration) (SM 9223B)		x	x	
EDB/DCBP	EPA 504.1	x		
EDB/DCBP and DBP	EPA 551.1	x	x	
EDTA and NTA	In House Method	x	x	
Endothall	EPA 548.1	x	x	
Enterococci	SM 9230B	x		x
Fecal Coliform (SM 9221 E (MTF/EC))		x		
Fecal Coliform (SM 9221 C, E (MTF/EC))				x
Fecal Coliform (Enumeration) (SM 9221E (MTF/EC))		x	x	
Fecal Coliform with Chlorine Present (SM 9221E)				x
Fecal Streptococci (SM 9230B)		x		x
Fluoride (SM 4500-F C)		x	x	x
Glyphosate (EPA 547)		x	x	
Gross Alpha/Beta (EPA 900.0)		x	x	x
HAA5/ Dalapon (EPA 552.3)		x	x	
Hardness (SM 2340B)		x	x	x
Heterotrophic Bacteria (In House Method)		x	x	
Heterotrophic Bacteria (SM 9215 B)		x	x	
Hexavalent Chromium (EPA 218.6)		x	x	x
Hexavalent Chromium (EPA 218.7)		x	x	
Hexavalent Chromium (SM 3500-Cr B or C (20th))				x

SPECIFIC TESTS	METHOD OR TECHNIQUE USED	Drinking Water	Food & Beverage	Waste Water
Hormones	EPA 539	x	x	
Hydroxide as OH Calc.	SM 2330B	x	x	
Kjeldahl Nitrogen	EPA 351.2			x
Mercury	EPA 245.1	x	x	x
Metals	EPA 200.7 / 200.8	x	x	x
Microcystin LR	ELISA	x	x	
NDMA	EPA 521	x	x	
Nitrate/Nitrite Nitrogen	EPA 353.2	x	x	x
OCL, Pesticides/PCB	EPA 505	x	x	
Ortho Phosphate	EPA 365.1	x	x	
Ortho Phosphate and Total Phosphorous	EPA 365.1/SM 4500-P E			x
Ortho Phosphorous	SM 4500P E	x	x	
Oxyhalides Disinfection Byproducts	EPA 317.0	x	x	
Perchlorate	EPA 331.0	x	x	
Perchlorate	EPA 314.0	x	x	
Perfluorinated Alkyl Acids	EPA 537	x	x	
pH	EPA 150.1	x		
pH	SM 4500-H+B	x	x	x
Phenylurea Pesticides/ Herbicides	In House Method	x	x	
Pseudomonas	IDEXX Pseudalert	x	x	
Radium-226	RA-226 GA	x	x	
Radium-228	RA-228 GA	x	x	
Radon-222	SM 7500RN	x	x	
Residue, Filterable	SM 2540C	x	x	x
Residue, Non-filterable	SM 2540D			x
Residue, Total	SM 2540B		x	x
Residue, Volatile	EPA 160.4			x
Semi-VOC	EPA 525.2	x	x	
Semi-VOC	EPA 625	x	x	x
Silica	SM 4500-Si D	x	x	x
Silica	SM 4500-SiO ₂ C	x		x
Sulfide	SM 4500-S ⁻² D			x
Sulfite	SM 4500-SO ³ B	x	x	x
Surfactants	SM 5540C	x	x	x
Taste and Odor Analytes	SM 6040E	x	x	
Total Coliform	SM 9221 A, B	x	x	
Total Coliform (Enumeration)	SM 9221 A, B, C	x	x	
Total Coliform / E. coli	Colisure	x	x	
Total Coliform	SM 9221B			x
Total Coliform with Chlorine Present	SM 9221B			x
Total Coliform / E.coli	SM 9223	x	x	
TOC	SM 5310C		x	x
TOC/DOC	SM 5310C	x	x	
TOX	SM 5320B			x
Total Phenols	EPA 420.1			x
Total Phenols	EPA 420.4	x	x	x
Total Phosphorous	SM 4500 P F			x
Turbidity	EPA 180.1	x	x	x
Turbidity	SM 2130B	x		x
Uranium by ICP/MS	EPA 200.8	x	x	
UV 254	SM 5910B	x		
VOC	EPA 524.2/EPA 524.3	x	x	
VOC	EPA 624	x	x	x
VOC	EPA SW 846 8260	x	x	
VOC	In House Method	x	x	
Yeast and Mold	SM 9610	x	x	

750 Royal Oaks Dr., Ste 100, Monrovia, CA 91016 Tel (626) 386-1100 Fax (626) 386-1101 <http://www.EatonAnalytical.com>

Acknowledgement of Samples Received

Addr: **Horsham Water & Sewer Authority**
617 Horsham Road
Horsham, PA 19044

Client ID: HORSHAM-PA
Folder #: 487436
Project: UCMR3
Sample Group: PA1460033/Horsham W&SA GW

Attn: Tina M. O'Rourke
Phone: (215) 672-8011


Project Manager: Thomas.D.French
Phone: (480) 778-1558

The following samples were received from you on **June 26, 2014**. They have been scheduled for the tests listed below each sample. If this information is incorrect, please contact your service representative. Thank you for using Eurofins Eaton Analytical.

Sample #	Sample ID	Sample Date
<u>201406260448</u>	00116-116-Well # 40 Sample Type: EP Sample Event: SE1 Facility ID: 00116 Sample Point ID: 116 PWSID: PA1460033 Static ID: EP @UCMR3 522 C @UCMR3 537	06/24/2014 1320
<u>201406260449</u>	FB:00116-116-Well # 40 Static ID: FB @UCMR3 537 FB	06/24/2014 1320

Test Description

- @UCMR3 522 C -- UCMR3 1,4-Dioxane by EPA 522
- @UCMR3 537 -- UCMR3 537
- @UCMR3 537 FB -- UCMR3 537



Eaton Analytical

750 Royal Oaks Drive, Suite 100, Monrovia, CA 91016-3629

Phone: 626 386 1100/ 800 566 LABS (800 566 5227)

Fax: 626 386 1101

Website: www.EatonAnalytical.com

PWSID: PA1460033
Example: (CA1234567)

UCMR3 CHAIN OF CUSTODY RECORD

EUROFINS EATON ANALYTICAL USE ONLY:

Folder No:

LOGIN COMMENTS:

SAMPLES CHECKED AGAINST COC BY: *JS*

SAMPLES LOGGED IN BY: *JS*

SAMPLE TEMP RECEIVED AT:

Colton / No. California / Arizona
 Monrovia

SAMPLES REC'D DAY OF COLLECTION? (check for yes)

°C (Compliance: ≤10°C for the first 48 hours or ≤6°C after 48 hours)

°C (Compliance: ≤10°C for the first 48 hours or ≤6°C after 48 hours)

Wet Ice No Ice

Partially Frozen Thawed

METHOD OF SHIPMENT: Pick-Up / Walk-In / FedEx / UPS / Area Fast / Top Line / Other: _____

TO BE COMPLETED BY SAMPLER:

COMPANY/AGENCY NAME: Aqua Pennsylvania, Inc.

PROJECT CODE: UCMR3-PA

COMPLIANCE SAMPLES x x

(check for yes)

Regulation: UCMR3

EPA CLIENT CODE: PHILLYSUB COC ID: PA1460033

SAMPLE GROUP: PA1460033/ Horsham Water & Sewer Authority

UNIQUE FIELD SAMPLE ID (per EPA Requirement) - 20 characters max

WATER SOURCE TYPE #13: GW SE1

SAMPLE POINT TYPE #14: EP

DISINFECTANT TYPE #15: _____

STD: X, 1 wk, 3 day, 2 day, 1 day

FACILITY ID (per EPA Requirement) - 5 characters Max: 00116-116

Well #40

SAMPLE DATE: 06/24/14

SAMPLE TIME: 13:20

UCMR3 200.8 - FB

UCMR3 200.8

UCMR3 218.7

UCMR3 Chlorate

UCMR3 524.3

UCMR3 524.3 - TB

UCMR3 522

UCMR3 537

UCMR3 537 - FB

UCMR3 539

UCMR3 539 - FB

SAMPLER COMMENTS

- (1) Water Source Type: SW: Surface Water GW: Ground Water GU: Ground Water under the direct influence of SW MX: Any Combination of previous three water types
- (2) Sample Event Code: SE1 (first) SE2 (second) SE3 (third) SE4 (fourth)
- (3) Sampling Point Type ID: EP: Entry Point to the distribution system MR: Distribution System sample at maximum residence time
- (4) Disinfectant Type: CLGA: Gaseous Chlorine CLOF: Offsite Generated Hypochlorite (stored as liquid form) CLON: Onsite Generated Hypochlorite (no storage) CAGC: Chloramine (formed from gaseous chlorine) CAOF: Chloramine (formed from onsite hypochlorite) CAON: Chloroamine (formed from onsite hypochlorite) CLDO: Chlorine Dioxide OZON: Ozone ULVL: Ultraviolet Light OTHD: All Other Types of Disinfectant NODU: No Disinfectant Used

* Field Blank (FB) or Trip Blank (TB) are analyzed only when associated samples have positive results (>MRL)

SAMPLED BY:	SIGNATURE	PRINT NAME	COMPANY	DATE	TIME
RELINQUISHED BY:		B. Pachik	Aqua PA	06/24/14	13:20
RECEIVED BY:					
RELINQUISHED BY:	<i>A. Nguyen</i>	A. Nguyen	Aqua PA	06/25/14	16:00
RECEIVED BY:	<i>W. Nguyen</i>		<i>EEA</i>	<i>06/26/14</i>	<i>11:17</i>

From: (610) 645-1176
Michael Senft
Aqua
762 West Lancaster Avenue

Bryn Mawr, PA 19010

Origin ID: WAYA



Ship Date: 25JUN14
ActWgt: 15.0 LB
CAD: 100061330/NET3490
Dims: 24 X 13 X 14 IN

Delivery Address Bar Code



SHIP TO: (626) 386-1100
LOGIN
MWH Americas, INC,
750 Royal Oaks Drive
Suite 100
Monrovia, CA 91016

BILL RECIPIENT

Ref # UCMR3
Invoice # 15-3031
PO #
Dept # 15-3031

1 of 4

THU - 26 JUN AA
STANDARD OVERNIGHT



TRK# 7704 1278 2010

0201

MASTER

NC WHPA

91016
CA-US
BUR



522GSAB04F220

After printing this label:

1. Use the 'Print' button on this page to print your label to your laser or inkjet printer.
2. Fold the printed page along the horizontal line.
3. Place label in shipping pouch and affix it to your shipment so that the barcode portion of the label can be read and scanned.

Warning: Use only the printed original label for shipping. Using a photocopy of this label for shipping purposes is fraudulent and could result in additional billing charges, along with the cancellation of your FedEx account number.

Use of this system constitutes your agreement to the service conditions in the current FedEx Service Guide, available on fedex.com. FedEx will not be responsible for any claim in excess of \$100 per package, whether the result of loss, damage, delay, non-delivery, misdelivery, or misinformation, unless you declare a higher value, pay an additional charge, document your actual loss and file a timely claim. Limitations found in the current FedEx Service Guide apply. Your right to recover from FedEx for any loss, including intrinsic value of the package, loss of sales, income interest, profit, attorney's fees, costs, and other forms of damage whether direct, incidental, consequential, or special is limited to the greater of \$100 or the authorized declared value. Recovery cannot exceed actual documented loss. Maximum for items of extraordinary value is \$1,000, e.g. jewelry, precious metals, negotiable instruments and other items listed in our Service Guide. Written claims must be filed within strict time limits, see current FedEx Service Guide.



Eaton Analytical

750 Royal Oaks Drive, Suite 100
Monrovia, California 91016-3629
Tel: (626) 386-1100
Fax: (626) 386-1101
1 800 566 LABS (1 800 566 5227)

Laboratory Comments
Report: 487436

Horsham Water & Sewer Authority
Tina M. O'Rourke
617 Horsham Road
Horsham, PA 19044

The Comments Report may be blank if there are no comments for this report.



Eaton Analytical

750 Royal Oaks Drive, Suite 100
Monrovia, California 91016-3629
Tel: (626) 386-1100
Fax: (626) 386-1101
1 800 566 LABS (1 800 566 5227)

UCMR Field Blank
Report: 487436

Horsham Water & Sewer Authority
Tina M. O'Rourke
617 Horsham Road
Horsham, PA 19044

Samples Received on:
06/26/2014

The results section will be blank if there are no exceedances of UCMR3 Field Blank criteria. Field Blank Evaluation is required for positive detection in the associated sample for Metals by 200.8, VOCs by 524.3, PFCs by 537, and Hormones by 539 (SS monitoring only). A detection on this report indicates need for re-sample for the associated site and test. Reference: UCMR3 Laboratory Approval Requirements and Information Document V2, May 2012 section 8.1 Field Blanks.

UCMR3 Field Blanks are not required to be analyzed, if the target analytes are not detected in the associated samples. In that event, the Field Blank data are not available (NA) for reporting.

Results Section

Analyzed	Analyte	Sample ID	Result	Units	UCMR Limit
----------	---------	-----------	--------	-------	------------

SUMMARY OF POSITIVE DATA ONLY

<u>Method</u>	<u>Method description</u>	<u>Positive Data Limit = UCMR Limit</u>
@UCMR3 200.8 FB	Metals	Any detection Greater than 1/3
@UCMR3 524.3 TB	Volatiles	MRL
@UCMR3 537 FB	Perfluorinated	Any detection Greater than 1/3
@UCMR3 539 FB	Hormones	MRL



Eaton Analytical

750 Royal Oaks Drive, Suite 100
Monrovia, California 91016-3629
Tel: (626) 386-1100
Fax: (626) 386-1101
1 800 566 LABS (1 800 566 5227)

Laboratory Hits
Report: 487436

Horsham Water & Sewer Authority
Tina M. O'Rourke
617 Horsham Road
Horsham, PA 19044

Samples Received on:
06/26/2014

Analyzed	Analyte	Sample ID	Result	Federal MCL	Units	MRL
	201406260448	<u>00116-116-Well # 40</u>				
07/03/2014 21:27	1,4-Dioxane		0.57		ug/L	0.07
07/02/2014 13:32	Perfluoro octanesulfonic acid - PFOS		1.0		ug/L	0.4
07/01/2014 21:44	Perfluoro-1-butanesulfonic acid -PFBS		0.11		ug/L	0.09
07/02/2014 13:32	Perfluoro-1-hexanesulfonic acid - PFHxS		0.59		ug/L	0.3
07/01/2014 21:44	Perfluoroheptanoic acid - PFHpA		0.039		ug/L	0.01
07/01/2014 21:44	Perfluorooctanoic acid - PFOA		0.063		ug/L	0.02

SUMMARY OF POSITIVE DATA ONLY



Eaton Analytical

750 Royal Oaks Drive, Suite 100
Monrovia, California 91016-3629
Tel: (626) 386-1100
Fax: (626) 386-1101
1 800 566 LABS (1 800 566 5227)

Laboratory Data
Report: 487436

Horsham Water & Sewer Authority
Tina M. O'Rourke
617 Horsham Road
Horsham, PA 19044

Samples Received on:
06/26/2014

Prepared	Analyzed	QC Ref #	Method	Analyte	Result	Units	MRL	Dilution
00116-116-Well # 40 (201406260448)					Sampled on 06/24/2014 1320			
Sample Type: EP								
Sample Event: SE1								
Facility ID: 00116								
Sample Point ID: 116								
PWSID: PA1460033								
Static ID: EP								
EPA 522 - UCMR3 1,4-Dioxane by EPA 522								
6/30/2014	07/03/2014	21:27	779457 (EPA 522)	1,4-Dioxane	0.57	ug/L	0.07	1
6/30/2014	07/03/2014	21:27	779457 (EPA 522)	Dioxane-d8	93	%		1
6/30/2014	07/03/2014	21:27	779457 (EPA 522)	THF-d8	80	%		1
EPA 537 - UCMR3 537								
	07/02/2014	13:32	778753 (EPA 537)	Perfluoro octanesulfonic acid - PFOS	1.0	ug/L	0.4	10
	07/01/2014	21:44	778753 (EPA 537)	Perfluoro-1-butanesulfonic acid -PFBS	0.11	ug/L	0.09	1
	07/02/2014	13:32	778753 (EPA 537)	Perfluoro-1-hexanesulfonic acid - PFHxS	0.59	ug/L	0.3	10
	07/01/2014	21:44	778753 (EPA 537)	Perfluoroheptanoic acid - PFHpA	0.039	ug/L	0.01	1
	07/01/2014	21:44	778753 (EPA 537)	Perfluoro-n-nonanoic acid -PFNA	ND	ug/L	0.02	1
	07/01/2014	21:44	778753 (EPA 537)	Perfluorooctanoic acid - PFOA	0.063	ug/L	0.02	1
	07/01/2014	21:44	778753 (EPA 537)	13C-PFDA - Surr#2	87	%		1
	07/01/2014	21:44	778753 (EPA 537)	13C-PFHxA - Surr#1	80	%		1
	07/01/2014	21:44	778753 (EPA 537)	13C-PFOA- IS#1	114	%		1
	07/01/2014	21:44	778753 (EPA 537)	13C-PFOS- IS#2	88	%		1
FB::00116-116-Well # 40 (201406260449)					Sampled on 06/24/2014 1320			
Static ID: FB								
EPA 537 - UCMR3 537								
	07/08/2014	18:02	779714 (EPA 537)	Perfluoro octanesulfonic acid - PFOS	ND	ug/L	0.04	1
	07/08/2014	18:02	779714 (EPA 537)	Perfluoro-1-butanesulfonic acid -PFBS	ND	ug/L	0.09	1
	07/08/2014	18:02	779714 (EPA 537)	Perfluoro-1-hexanesulfonic acid - PFHxS	ND	ug/L	0.03	1
	07/08/2014	18:02	779714 (EPA 537)	Perfluoroheptanoic acid - PFHpA	ND	ug/L	0.01	1
	07/08/2014	18:02	779714 (EPA 537)	Perfluoro-n-nonanoic acid -PFNA	ND	ug/L	0.02	1
	07/08/2014	18:02	779714 (EPA 537)	Perfluorooctanoic acid - PFOA	ND	ug/L	0.02	1
	07/08/2014	18:02	779714 (EPA 537)	13C-PFDA - Surr#2	96	%		1
	07/08/2014	18:02	779714 (EPA 537)	13C-PFHxA - Surr#1	91	%		1
	07/08/2014	18:02	779714 (EPA 537)	13C-PFOA- IS#1	115	%		1
	07/08/2014	18:02	779714 (EPA 537)	13C-PFOS- IS#2	108	%		1

Rounding on totals after summation.
(c) - indicates calculated results

750 Royal Oaks Drive, Suite 100
Monrovia, California 91016-3629
Tel: (626) 386-1100
Fax: (626) 386-1101
1 800 566 LABS (1 800 566 5227)

Horsham Water & Sewer Authority

QC Ref # 778753 - UCMR3 537

201406260448	00116-116-Well # 40
201406260448	00116-116-Well # 40
201406260448	00116-116-Well # 40

Analysis Date: 07/01/2014

Analyzed by: 1CL
Analyzed by: 1CL
Analyzed by: 1CL

QC Ref # 779457 - UCMR3 1,4-Dioxane by EPA 522

201406260448	00116-116-Well # 40
--------------	---------------------

Analysis Date: 07/03/2014

Analyzed by: CRW

QC Ref # 779714 - UCMR3 537

201406260449	FB::00116-116-Well # 40
--------------	-------------------------

Analysis Date: 07/08/2014

Analyzed by: 1CL

750 Royal Oaks Drive, Suite 100
Monrovia, California 91016-3629
Tel: (626) 386-1100
Fax: (626) 386-1101
1 800 566 LABS (1 800 566 5227)

Horsham Water & Sewer Authority

QC Type	Analyte	Native	Spiked	Recovered	Units	Yield (%)	Limits (%)	RPDLimit (%)	RPD%
QC Ref# 778753 - UCMR3 537 by EPA 537						Analysis Date: 07/01/2014			
CCCH	13C-PFDA - Surr#2 (S)			101	%	101	(70-130)		
CCCL	13C-PFDA - Surr#2 (S)			99.3	%	99	(70-130)		
CCCM	13C-PFDA - Surr#2 (S)			97.8	%	98	(70-130)		
MBLK_HI	13C-PFDA - Surr#2 (S)			86.4	%	86	(70-130)		
MRLHI	13C-PFDA - Surr#2 (S)			86.6	%	87	(70-130)		
MS2_201406260469	13C-PFDA - Surr#2 (S)			89.8	%	90	(70-130)		
MSD2_201406260469	13C-PFDA - Surr#2 (S)			85.7	%	86	(70-130)		
QCS	13C-PFDA - Surr#2 (S)			102	%	102	(70-130)		
CCCH	13C-PFHxA - Surr#1 (S)			101	%	101	(70-130)		
CCCL	13C-PFHxA - Surr#1 (S)			100	%	100	(70-130)		
CCCM	13C-PFHxA - Surr#1 (S)			101	%	101	(70-130)		
MBLK_HI	13C-PFHxA - Surr#1 (S)			90.6	%	91	(70-130)		
MRLHI	13C-PFHxA - Surr#1 (S)			91.7	%	92	(70-130)		
MS2_201406260469	13C-PFHxA - Surr#1 (S)			81.9	%	82	(70-130)		
MSD2_201406260469	13C-PFHxA - Surr#1 (S)			80.6	%	81	(70-130)		
QCS	13C-PFHxA - Surr#1 (S)			101	%	101	(70-130)		
CCCH	13C-PFOA- IS#1 (I)			101	%	101	(50-150)		
CCCL	13C-PFOA- IS#1 (I)			101	%	101	(50-150)		
CCCM	13C-PFOA- IS#1 (I)			98.4	%	98	(50-150)		
MBLK_HI	13C-PFOA- IS#1 (I)			122	%	122	(50-150)		
MRLHI	13C-PFOA- IS#1 (I)			119	%	119	(50-150)		
MS2_201406260469	13C-PFOA- IS#1 (I)			114	%	114	(50-150)		
MSD2_201406260469	13C-PFOA- IS#1 (I)			116	%	116	(50-150)		
QCS	13C-PFOA- IS#1 (I)			96.5	%	97	(50-150)		
CCCH	13C-PFOS- IS#2 (I)			103	%	103	(50-150)		
CCCL	13C-PFOS- IS#2 (I)			100	%	100	(50-150)		
CCCM	13C-PFOS- IS#2 (I)			101	%	101	(50-150)		
MBLK_HI	13C-PFOS- IS#2 (I)			123	%	123	(50-150)		
MRLHI	13C-PFOS- IS#2 (I)			118	%	119	(50-150)		
MS2_201406260469	13C-PFOS- IS#2 (I)			117	%	117	(50-150)		
MSD2_201406260469	13C-PFOS- IS#2 (I)			117	%	117	(50-150)		
QCS	13C-PFOS- IS#2 (I)			99.5	%	99	(50-150)		
CCCH	Perfluoro octanesulfonic acid - PFOS		0.13	0.121	ug/L	95	(70-130)		
CCCL	Perfluoro octanesulfonic acid - PFOS		0.032	0.0310	ug/L	97	(50-150)		
CCCM	Perfluoro octanesulfonic acid - PFOS		0.064	0.0613	ug/L	96	(70-130)		
MBLK_HI	Perfluoro octanesulfonic acid - PFOS	ND		<0.01333	ug/L				

Spike recovery is already corrected for native results.

Spikes which exceed Limits and Method Blanks with positive results are highlighted by Underlining.

Criteria for MS and Dup are advisory only, batch control is based on LCS. Criteria for duplicates are advisory only, unless otherwise specified in the method.

RPD not calculated for LCS2 when different a concentration than LCS1 is used.

RPD not calculated for Duplicates when the result is not five times the MRL (Minimum Reporting Level).

(S) - Indicates surrogate compound.

(I) - Indicates internal standard compound.

750 Royal Oaks Drive, Suite 100
Monrovia, California 91016-3629
Tel: (626) 386-1100
Fax: (626) 386-1101
1 800 566 LABS (1 800 566 5227)

Horsham Water & Sewer Authority

QC Type	Analyte	Native	Spiked	Recovered	Units	Yield (%)	Limits (%)	RPDLimit (%)	RPD%
MRLHI	Perfluoro octanesulfonic acid - PFOS		0.04	0.0340	ug/L	85	(50-150)		
MS2_201406260469	Perfluoro octanesulfonic acid - PFOS	ND	0.08	0.0798	ug/L	89	(70-130)		
MSD2_201406260469	Perfluoro octanesulfonic acid - PFOS	ND	0.08	0.0794	ug/L	89	(70-130)	30	0.50
QCS	Perfluoro octanesulfonic acid - PFOS		0.048	0.0472	ug/L	99	(70-130)		
CCCH	Perfluoro-1-butanefulfonic acid -PFBS		0.29	0.282	ug/L	97	(70-130)		
CCCL	Perfluoro-1-butanefulfonic acid -PFBS		0.078	0.0771	ug/L	99	(50-150)		
CCCM	Perfluoro-1-butanefulfonic acid -PFBS		0.15	0.149	ug/L	102	(70-130)		
MBLK_HI	Perfluoro-1-butanefulfonic acid -PFBS	ND		<0.03033	ug/L				
MRLHI	Perfluoro-1-butanefulfonic acid -PFBS		0.09	0.0851	ug/L	95	(50-150)		
MS2_201406260469	Perfluoro-1-butanefulfonic acid -PFBS	ND	0.18	0.177	ug/L	96	(70-130)		
MSD2_201406260469	Perfluoro-1-butanefulfonic acid -PFBS	ND	0.18	0.176	ug/L	96	(70-130)	30	0.57
QCS	Perfluoro-1-butanefulfonic acid -PFBS		0.044	0.0496	ug/L	112	(70-130)		
CCCH	Perfluoro-1-hexanesulfonic acid - PFHxS		0.096	0.0899	ug/L	94	(70-130)		
CCCL	Perfluoro-1-hexanesulfonic acid - PFHxS		0.024	0.0238	ug/L	99	(50-150)		
CCCM	Perfluoro-1-hexanesulfonic acid - PFHxS		0.048	0.0447	ug/L	93	(70-130)		
MBLK_HI	Perfluoro-1-hexanesulfonic acid - PFHxS	ND		<0.0100	ug/L				
MRLHI	Perfluoro-1-hexanesulfonic acid - PFHxS		0.03	0.0262	ug/L	87	(50-150)		
MS2_201406260469	Perfluoro-1-hexanesulfonic acid - PFHxS	ND	0.06	0.0587	ug/L	92	(70-130)		
MSD2_201406260469	Perfluoro-1-hexanesulfonic acid - PFHxS	ND	0.06	0.0584	ug/L	91	(70-130)	30	0.51
QCS	Perfluoro-1-hexanesulfonic acid - PFHxS		0.048	0.0448	ug/L	94	(70-130)		
CCCH	Perfluoroheptanoic acid - PFHpA		0.032	0.0317	ug/L	99	(70-130)		
CCCL	Perfluoroheptanoic acid - PFHpA		0.008	0.00826	ug/L	103	(50-150)		
CCCM	Perfluoroheptanoic acid - PFHpA		0.016	0.0158	ug/L	99	(70-130)		
MBLK_HI	Perfluoroheptanoic acid - PFHpA	ND		<0.00333	ug/L				
MRLHI	Perfluoroheptanoic acid - PFHpA		0.01	0.00881	ug/L	88	(50-150)		
MS2_201406260469	Perfluoroheptanoic acid - PFHpA	ND	0.02	0.0214	ug/L	90	(70-130)		
MSD2_201406260469	Perfluoroheptanoic acid - PFHpA	ND	0.02	0.0212	ug/L	89	(70-130)	30	0.94
QCS	Perfluoroheptanoic acid - PFHpA		0.05	0.0543	ug/L	109	(70-130)		
CCCH	Perfluoro-n-nonanoic acid -PFNA		0.064	0.0639	ug/L	100	(70-130)		
CCCL	Perfluoro-n-nonanoic acid -PFNA		0.016	0.0171	ug/L	107	(50-150)		
CCCM	Perfluoro-n-nonanoic acid -PFNA		0.032	0.0337	ug/L	105	(70-130)		
MBLK_HI	Perfluoro-n-nonanoic acid -PFNA	ND		<0.00666	ug/L				
MRLHI	Perfluoro-n-nonanoic acid -PFNA		0.02	0.0185	ug/L	92	(50-150)		
MS2_201406260469	Perfluoro-n-nonanoic acid -PFNA	ND	0.04	0.0388	ug/L	93	(70-130)		
MSD2_201406260469	Perfluoro-n-nonanoic acid -PFNA	ND	0.04	0.0384	ug/L	92	(70-130)	30	1.0
QCS	Perfluoro-n-nonanoic acid -PFNA		0.05	0.0490	ug/L	98	(70-130)		
CCCH	Perfluorooctanoic acid - PFOA		0.064	0.0631	ug/L	99	(70-130)		
CCCL	Perfluorooctanoic acid - PFOA		0.016	0.0163	ug/L	102	(50-150)		

Spike recovery is already corrected for native results.

Spikes which exceed Limits and Method Blanks with positive results are highlighted by Underlining.

Criteria for MS and Dup are advisory only, batch control is based on LCS. Criteria for duplicates are advisory only, unless otherwise specified in the method.

RPD not calculated for LCS2 when different a concentration than LCS1 is used.

RPD not calculated for Duplicates when the result is not five times the MRL (Minimum Reporting Level).

(S) - Indicates surrogate compound.

(I) - Indicates internal standard compound.

750 Royal Oaks Drive, Suite 100
 Monrovia, California 91016-3629
 Tel: (626) 386-1100
 Fax: (626) 386-1101
 1 800 566 LABS (1 800 566 5227)

Laboratory QC
 Report: 487436

Horsham Water & Sewer Authority

QC Type	Analyte	Native	Spiked	Recovered	Units	Yield (%)	Limits (%)	RPDLimit (%)	RPD%
CCCM	Perfluorooctanoic acid - PFOA		0.032	0.0326	ug/L	102	(70-130)		
MBLK_HI	Perfluorooctanoic acid - PFOA	ND		<0.00666	ug/L				
MRLHI	Perfluorooctanoic acid - PFOA		0.02	0.0184	ug/L	92	(50-150)		
MS2_201406260469	Perfluorooctanoic acid - PFOA	ND	0.04	0.0444	ug/L	95	(70-130)		
MSD2_201406260469	Perfluorooctanoic acid - PFOA	ND	0.04	0.0434	ug/L	93	(70-130)	30	2.3
QCS	Perfluorooctanoic acid - PFOA		0.05	0.0511	ug/L	102	(70-130)		

QC Ref# 779457 - UCMR3 1,4-Dioxane by EPA 522 by EPA 522

Analysis Date: 07/03/2014

CCCH	1,4-Dioxane		50	53.6	ug/L	107	(70-130)		
CCCL	1,4-Dioxane		0.07	0.0670	ug/L	96	(50-150)		
CCCM	1,4-Dioxane		20	20.9	ug/L	105	(70-130)		
LCS1	1,4-Dioxane		20	16.8	ug/L	84	(70-130)		
MBLK	1,4-Dioxane			<0.023	ug/L				
MRL_CHK	1,4-Dioxane		0.07	0.0680	ug/L	97	(50-150)		
MS_201406250115	1,4-Dioxane	ND	20	16.9	ug/L	84	(70-130)		
MSD_201406250115	1,4-Dioxane	ND	20	16.7	ug/L	84	(70-130)	20	1.2
CCCH	Dioxane-d8			112	%	113	(70-130)		
CCCL	Dioxane-d8			106	%	106	(70-130)		
CCCM	Dioxane-d8			115	%	115	(70-130)		
LCS1	Dioxane-d8			90.3	%	90	(70-130)		
MBLK	Dioxane-d8			88.6	%				
MRL_CHK	Dioxane-d8			91.2	%	91	(70-130)		
MS_201406250115	Dioxane-d8	90		89.9	%	90	(70-130)		
MSD_201406250115	Dioxane-d8	90		89.8	%	90	(70-130)		
CCCH	THF-d8			75.9	%	76	(50-150)		
CCCL	THF-d8			77.2	%	77	(50-150)		
CCCM	THF-d8			71.0	%	71	(50-150)		
LCS1	THF-d8			68.9	%	69	(50-150)		
MBLK	THF-d8			69.9	%				
MRL_CHK	THF-d8			69.5	%	70	(50-150)		
MS_201406250115	THF-d8	71		65.7	%	66	(50-150)		
MSD_201406250115	THF-d8	71		75.5	%	76	(50-150)		

QC Ref# 779714 - UCMR3 537 by EPA 537

Analysis Date: 07/08/2014

CCCH	13C-PFDA - Surr#2 (S)			97.2	%	97	(70-130)		
CCCL	13C-PFDA - Surr#2 (S)			98.6	%	99	(70-130)		
CCCM	13C-PFDA - Surr#2 (S)			95.8	%	96	(70-130)		
MBLK_HI	13C-PFDA - Surr#2 (S)			90.5	%	91	(70-130)		
MRLHI	13C-PFDA - Surr#2 (S)			92.4	%	92	(70-130)		

Spike recovery is already corrected for native results.

Spikes which exceed Limits and Method Blanks with positive results are highlighted by Underlining.

Criteria for MS and Dup are advisory only, batch control is based on LCS. Criteria for duplicates are advisory only, unless otherwise specified in the method.

RPD not calculated for LCS2 when different a concentration than LCS1 is used.

RPD not calculated for Duplicates when the result is not five times the MRL (Minimum Reporting Level).

(S) - Indicates surrogate compound.

(I) - Indicates internal standard compound.

750 Royal Oaks Drive, Suite 100
 Monrovia, California 91016-3629
 Tel: (626) 386-1100
 Fax: (626) 386-1101
 1 800 566 LABS (1 800 566 5227)

Horsham Water & Sewer Authority

QC Type	Analyte	Native	Spiked	Recovered	Units	Yield (%)	Limits (%)	RPDLimit (%)	RPD%
MS1_201407020552	13C-PFDA - Surr#2 (S)			89.7	%	90	(70-130)		
MSD1_201407020552	13C-PFDA - Surr#2 (S)			91.6	%	92	(70-130)		
QCS	13C-PFDA - Surr#2 (S)			92.9	%	93	(70-130)		
CCCH	13C-PFHxA - Surr#1 (S)			94.8	%	95	(70-130)		
CCCL	13C-PFHxA - Surr#1 (S)			98.8	%	99	(70-130)		
CCCM	13C-PFHxA - Surr#1 (S)			95.9	%	96	(70-130)		
MBLK_HI	13C-PFHxA - Surr#1 (S)			93.6	%	94	(70-130)		
MRLHI	13C-PFHxA - Surr#1 (S)			96.3	%	96	(70-130)		
MS1_201407020552	13C-PFHxA - Surr#1 (S)			95.2	%	95	(70-130)		
MSD1_201407020552	13C-PFHxA - Surr#1 (S)			99.8	%	100	(70-130)		
QCS	13C-PFHxA - Surr#1 (S)			95.8	%	96	(70-130)		
CCCH	13C-PFOA- IS#1 (I)			105	%	105	(50-150)		
CCCL	13C-PFOA- IS#1 (I)			101	%	101	(50-150)		
CCCM	13C-PFOA- IS#1 (I)			104	%	104	(50-150)		
MBLK_HI	13C-PFOA- IS#1 (I)			110	%	110	(50-150)		
MRLHI	13C-PFOA- IS#1 (I)			110	%	110	(50-150)		
MS1_201407020552	13C-PFOA- IS#1 (I)			106	%	106	(50-150)		
MSD1_201407020552	13C-PFOA- IS#1 (I)			103	%	103	(50-150)		
QCS	13C-PFOA- IS#1 (I)			98.9	%	99	(50-150)		
CCCH	13C-PFOS- IS#2 (I)			106	%	106	(50-150)		
CCCL	13C-PFOS- IS#2 (I)			103	%	103	(50-150)		
CCCM	13C-PFOS- IS#2 (I)			103	%	103	(50-150)		
MBLK_HI	13C-PFOS- IS#2 (I)			109	%	109	(50-150)		
MRLHI	13C-PFOS- IS#2 (I)			108	%	108	(50-150)		
MS1_201407020552	13C-PFOS- IS#2 (I)			108	%	108	(50-150)		
MSD1_201407020552	13C-PFOS- IS#2 (I)			107	%	107	(50-150)		
QCS	13C-PFOS- IS#2 (I)			99.3	%	99	(50-150)		
CCCH	Perfluoro octanesulfonic acid - PFOS		0.13	0.124	ug/L	97	(70-130)		
CCCL	Perfluoro octanesulfonic acid - PFOS		0.032	0.0315	ug/L	99	(50-150)		
CCCM	Perfluoro octanesulfonic acid - PFOS		0.064	0.0633	ug/L	99	(70-130)		
MBLK_HI	Perfluoro octanesulfonic acid - PFOS	ND		<0.01333	ug/L				
MRLHI	Perfluoro octanesulfonic acid - PFOS		0.04	0.0427	ug/L	107	(50-150)		
MS1_201407020552	Perfluoro octanesulfonic acid - PFOS	ND	0.04	0.0412	ug/L	102	(50-150)		
MSD1_201407020552	Perfluoro octanesulfonic acid - PFOS	ND	0.04	0.0401	ug/L	100	(50-150)	30	2.7
QCS	Perfluoro octanesulfonic acid - PFOS		0.048	0.0472	ug/L	99	(70-130)		
CCCH	Perfluoro-1-butanesulfonic acid -PFBS		0.29	0.292	ug/L	100	(70-130)		
CCCL	Perfluoro-1-butanesulfonic acid -PFBS		0.078	0.0766	ug/L	98	(50-150)		
CCCM	Perfluoro-1-butanesulfonic acid -PFBS		0.15	0.155	ug/L	107	(70-130)		

Spike recovery is already corrected for native results.

 Spikes which exceed Limits and Method Blanks with positive results are highlighted by Underlining.

Criteria for MS and Dup are advisory only, batch control is based on LCS. Criteria for duplicates are advisory only, unless otherwise specified in the method.

RPD not calculated for LCS2 when different a concentration than LCS1 is used.

RPD not calculated for Duplicates when the result is not five times the MRL (Minimum Reporting Level).

(S) - Indicates surrogate compound.

(I) - Indicates internal standard compound.

750 Royal Oaks Drive, Suite 100
 Monrovia, California 91016-3629
 Tel: (626) 386-1100
 Fax: (626) 386-1101
 1 800 566 LABS (1 800 566 5227)

Laboratory QC
 Report: 487436

Horsham Water & Sewer Authority

QC Type	Analyte	Native	Spiked	Recovered	Units	Yield (%)	Limits (%)	RPDLimit (%)	RPD%
MBLK_HI	Perfluoro-1-butanefulfonic acid -PFBS	ND		<0.03033	ug/L				
MRLHI	Perfluoro-1-butanefulfonic acid -PFBS		0.09	0.107	ug/L	119	(50-150)		
MS1_201407020552	Perfluoro-1-butanefulfonic acid -PFBS	ND	0.091	0.104	ug/L	114	(50-150)		
MSD1_201407020552	Perfluoro-1-butanefulfonic acid -PFBS	ND	0.091	0.104	ug/L	115	(50-150)	30	0.0
QCS	Perfluoro-1-butanefulfonic acid -PFBS		0.044	0.0508	ug/L	114	(70-130)		
CCCH	Perfluoro-1-hexanesulfonic acid - PFHxS		0.096	0.0904	ug/L	94	(70-130)		
CCCL	Perfluoro-1-hexanesulfonic acid - PFHxS		0.024	0.0233	ug/L	97	(50-150)		
CCCM	Perfluoro-1-hexanesulfonic acid - PFHxS		0.048	0.0470	ug/L	98	(70-130)		
MBLK_HI	Perfluoro-1-hexanesulfonic acid - PFHxS	ND		<0.0100	ug/L				
MRLHI	Perfluoro-1-hexanesulfonic acid - PFHxS		0.03	0.0323	ug/L	108	(50-150)		
MS1_201407020552	Perfluoro-1-hexanesulfonic acid - PFHxS	ND	0.03	0.0304	ug/L	101	(50-150)		
MSD1_201407020552	Perfluoro-1-hexanesulfonic acid - PFHxS	ND	0.03	0.0310	ug/L	103	(50-150)	30	2.0
QCS	Perfluoro-1-hexanesulfonic acid - PFHxS		0.048	0.0451	ug/L	95	(70-130)		
CCCH	Perfluoroheptanoic acid - PFHpA		0.032	0.0314	ug/L	98	(70-130)		
CCCL	Perfluoroheptanoic acid - PFHpA		0.008	0.00801	ug/L	100	(50-150)		
CCCM	Perfluoroheptanoic acid - PFHpA		0.016	0.0164	ug/L	103	(70-130)		
MBLK_HI	Perfluoroheptanoic acid - PFHpA	ND		<0.00333	ug/L				
MRLHI	Perfluoroheptanoic acid - PFHpA		0.01	0.0109	ug/L	109	(50-150)		
MS1_201407020552	Perfluoroheptanoic acid - PFHpA	ND	0.01	0.0108	ug/L	107	(50-150)		
MSD1_201407020552	Perfluoroheptanoic acid - PFHpA	ND	0.01	0.0111	ug/L	110	(50-150)	30	2.7
QCS	Perfluoroheptanoic acid - PFHpA		0.05	0.0527	ug/L	105	(70-130)		
CCCH	Perfluoro-n-nonanoic acid -PFNA		0.064	0.0618	ug/L	97	(70-130)		
CCCL	Perfluoro-n-nonanoic acid -PFNA		0.016	0.0168	ug/L	105	(50-150)		
CCCM	Perfluoro-n-nonanoic acid -PFNA		0.032	0.0328	ug/L	103	(70-130)		
MBLK_HI	Perfluoro-n-nonanoic acid -PFNA	ND		<0.00666	ug/L				
MRLHI	Perfluoro-n-nonanoic acid -PFNA		0.02	0.0220	ug/L	110	(50-150)		
MS1_201407020552	Perfluoro-n-nonanoic acid -PFNA	ND	0.02	0.0218	ug/L	109	(50-150)		
MSD1_201407020552	Perfluoro-n-nonanoic acid -PFNA	ND	0.02	0.0224	ug/L	112	(50-150)	30	2.3
QCS	Perfluoro-n-nonanoic acid -PFNA		0.05	0.0451	ug/L	90	(70-130)		
CCCH	Perfluorooctanoic acid - PFOA		0.064	0.0643	ug/L	101	(70-130)		
CCCL	Perfluorooctanoic acid - PFOA		0.016	0.0164	ug/L	102	(50-150)		
CCCM	Perfluorooctanoic acid - PFOA		0.032	0.0329	ug/L	103	(70-130)		
MBLK_HI	Perfluorooctanoic acid - PFOA	ND		<0.00666	ug/L				
MRLHI	Perfluorooctanoic acid - PFOA		0.02	0.0229	ug/L	115	(50-150)		
MS1_201407020552	Perfluorooctanoic acid - PFOA	ND	0.02	0.0224	ug/L	107	(50-150)		
MSD1_201407020552	Perfluorooctanoic acid - PFOA	ND	0.02	0.0228	ug/L	109	(50-150)	30	1.8
QCS	Perfluorooctanoic acid - PFOA		0.05	0.0500	ug/L	100	(70-130)		

Spike recovery is already corrected for native results.

Spikes which exceed Limits and Method Blanks with positive results are highlighted by Underlining.

Criteria for MS and Dup are advisory only, batch control is based on LCS. Criteria for duplicates are advisory only, unless otherwise specified in the method.

RPD not calculated for LCS2 when different a concentration than LCS1 is used.

RPD not calculated for Duplicates when the result is not five times the MRL (Minimum Reporting Level).

(S) - Indicates surrogate compound.

(I) - Indicates internal standard compound.